

RIGHT - OF - WAY		CROSSING		GWA-FL-GI-010.000		GWA-FL-GI-012.000		GWA-FL-GI-012.001.CR		GWA-FL-GI-014.000		GWA-FL-GI-016.000		GWA-FL-GI-014.070		GWA-FL-GI-026.000	
TRACT NUMBERS																	
RODDAGE		78.0		78.0		4.8		76.1		81.7		2.4					
SURVEY DATA		SURVEY COMPANY: FIELD BOOK: PAGES: 16487+00 TO 16489+08 16489+08 TO 16512+75 16512+75 TO 16513+65 16513+65 TO 16519+70 16519+70 TO 16526+11 16526+11 TO 16539+65 16539+65 TO 16540+00 16487+00 TO 16489+08 16489+08 TO 16512+75 16512+75 TO 16513+65 16513+65 TO 16519+70 16519+70 TO 16526+11 16526+11 TO 16539+65 16539+65 TO 16540+00															
CLASS LOCATION		CLASS 1															
MINIMUM DEPTH OF COVER		4' 5' 4' 5' 4' 5' 3' 5' 3' 5' 3' 5' 3'															
PIPE MATERIAL		36" 3R, FITTING SET ON WEIGHT, GPW, GEOTEXTILE PIPE WEIGHT															

ALIGNMENT DETAIL

PROPOSED PIPELINE
 PROPOSED PERMANENT EASEMENT
 TEMP WORKSPACE
 ADD. TEMP WORKSPACE
 EASEMENT LINE
 CL STREAM/CREEK/DITCH
 EDGE OF WATER
 CL LEVEE
 FIELD DELINEATED WETLAND
 STREAM/DRAIN/WATERBODY BNDRY
 CL ROAD
 EDGE OF ROAD/PAVEMENT/CURB
 CL CULVERT
 CL RAILROAD
 ACCESS ROAD (PAR/TAR)
 STRUCTURE
 CONTOUR MAJOR (EVERY 10')
 CONTOUR MINOR (EVERY 2')
 PIPELINE MILEPOST
 PIPELINE MILEPOST 10TH
 PROPERTY LINE
 UNDERGROUND WATERLINE
 UNDERGROUND COM. CABLE
 UNDERGROUND POWERLINE
 UNDERGROUND SANITARY SEWER
 OVERHEAD POWERLINE
 OVERHEAD TELEPHONE
 VERIFIED PIPELINE
 FENCE
 TOP / TOE

TRANS. TOWER
 GUY ANCHOR
 HDD ENTRY/EXIT
 FIRE HYDRANT
 UTILITY POLE
 AERIAL MARKER
 ELEC. WATER, SAN. SEWER, GAS
 TELE. & STORM DRAIN MANHOLES

WELL
 SEPTIC
 VALVE
 METER
 SPREAD BREAK

DATE OF AERIAL PHOTOGRAPHY: DECEMBER 13, 2013



REFERENCE DRAWING		GWA-FL-GI-012.001.CR															
ENVIRONMENTAL SURVEY DATA																	

SENSITIVE AREAS		6a, 6b, 8, 18															
------------------------	--	---------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

PROFILE


SCALE:
 HORIZONTAL: 1" = 200'
 VERTICAL: 1" = 200'

THE LOCATION OF TRENCH PLUGS AND SLOPE BREAKERS ARE INTENDED TO BE USED AS A GUIDELINE ONLY. EXACT LOCATION TO BE DETERMINED IN THE FIELD AS DIRECTED BY THE CHIEF INSPECTOR.

SLOPE BREAKERS/ARROW INDICATES DIRECTION

TRENCH PLUG
 CP TEST STATION
 RECTIFIER
 DECOUPLER

SLOPE BREAKER & TRENCH PLUG SPACING		
CODE	% SLOPE	SPACING
A	< 5%	NO STRUCTURE
B	5 - 15%	300 FT
C	15 - 30%	200 FT
D	> 30%	100 FT



HYDROSTATIC TEST SECTION		TEST SECTION 24															
REFERENCE DRAWINGS		REVISIONS				MATERIALS				ENGINEERING APPROVALS				SABAL TRAIL PROJECT PROPOSED 36" PIPELINE STA. 16487+00 TO STA. 16540+00 ALIGNMENT SHEET LOC. GILCHRIST COUNTY, FLORIDA YEAR: 2017 SHEET: 315 OF 492 SCALE: 1" = 200' DWG. 1657-PL-DG-70197-315 REV. 1			
DWG. NO.	DESCRIPTION	REV	DRN	DATE	DESCRIPTION	ITEM NO.	DESCRIPTION	QTY	TITLE	SIGNATURE	DATE	SIGNATURE	DATE				
		0		06/29/2015	ISSUED FOR BID	1	36" O.D. x 0.520" W.T., API 5L X70, FBE 16 MILS w/I.D. EPOXY 1.7 MILS	5165 LF	FRS		06/29/2015	FRS	03/14/2016				
		1		03/14/2016	ISSUED FOR CONSTRUCTION	3	36" O.D. x 0.750" W.T., API 5L X70, FBE 16 MILS, w/I.D. EPOXY 1.7 MILS	45 LF	DRS		06/29/2015	JC	03/14/2016				
						4	36" O.D. x 0.750" W.T., API 5L X70, FBE 16 MILS, ARO 24 MILS, w/I.D. EPOXY 1.7 MILS	90 LF									

Document Path: H:\GIS\1657-PL-DG-70197-315.mxd