



DISCLAIMER: UNIVERSALPEGASUS INTERNATIONAL MAKES NO WARRANTY (EXPRESSED, IMPLIED OR OTHERWISE) THAT THE INFORMATION CONTAINED HEREIN IS ACCURATE OR COMPLETE AS TO ANY AND ALL SUBSURFACE CONDITIONS AND CONFORMATION. ANY RELIANCE CONTRACTOR PLACES ON THE INFORMATION CONTAINED HEREIN AS TO SUCH CONDITIONS, IS DONE SO AT ITS OWN RISK AND EXPENSE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE STATE "ONE CALL" SYSTEM PRIOR TO ANY EXCAVATION.

SURVEY DATA		STATIONING	
MATCHLINE 90+00	90+00	MATCHLINE 130+00	130+00

ENGINEERING DATA		MATERIAL	
REFERENCE DRAWING	21040-440-PMW-20073	21040-505-HDW-21022	
CLASS LOCATION	Class III		
MINIMUM DEPTH OF COVER	SEE REF DWG		
AC MITIGATION / CATHODIC PROTECTION	774' of double ribbon (two 387' sections either side of pipeline) DCP-4A		

ENVIRONMENTAL DATA		STATIONS	
WATERBODY/WETLAND CROSSINGS	W-032	W-032	W-033
WATERBODY/WETLAND LENGTH	465'	1053'	379'
PERMANENT EROSION CONTROL	THIS BAND NOT UTILIZED		
THREATENED AND ENDANGERED SPECIES	Potential Sand Skink Habitat		

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS		GENERAL INFORMATION		LEGEND		REVISIONS			APPROVALS					
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.	HDD PIPE	PIPELINE ROUTE	PERMANENT ROW	NO.	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.	
4	2420	FT	36" O.D. x 0.750" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE & 24-30 MILS ARO	0	EA	SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.	LINE PIPE	FENCE	TEMPORARY WORKSPACE							CHECKED BY:	MJ	MAINTENANCE OPERATION REGION	
5	1580	FT	36" O.D. x 0.750" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	2	EA	PIPELINE MARKERS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.	3R RAD FIT	POWER LINE	ADDITIONAL TEMPORARY WORKSPACE	1	IFC (UPDATE ENV., RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG	PROJECT MANAGER	RG	MIN. TEST PRESSURE 1816 PSI	
FITTINGS SUMMARY				CONTINUOUS CONCRETE COATING				SPECIAL NOTES		4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.	INDUCTION BEND	TELEPHONE LINE	NON FORESTED WETLAND	0	ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG	PROJECT DEF. NO.		DESIGN PRESSURE 1440 PSI
PIPE ASSEMBLIES				PIPE COATING DATA				SPECIAL NOTES		5. ADDITIONAL WARNING SIGNS MAY BE REQUIRED AS DICTATED BY CONSTRUCTION CONTRACT.	CONT. CONC. COAT.	SEWER LINE	FORESTED WETLAND	APPROVAL			COMPANY					
PIPE ASSEMBLIES				PIPE COATING DATA				SPECIAL NOTES		6. MAP PROJECTION: NAD 1983 HARN STATE PLANE FLORIDA EAST FIPS 0901 FEET. VERTICAL DATUM: NAVD 88.	CONC. CONC. COAT.	UTILITY LINE	WATERBODY									
PIPE ASSEMBLIES				PIPE COATING DATA				SPECIAL NOTES		1. INDUCTION BEND QUANTITIES ALONG WITH THEIR DESCRIPTIONS ARE LOCATED ON DRAWING 21040-505-FBW-00001.	BY MOV. BV & CV	GENERAL SURVEY	WETLAND / WATERBODY NAME									
PIPE ASSEMBLIES				PIPE COATING DATA				SPECIAL NOTES		2. 3' - SEE ARK DRAWING PACKAGE FOR ANODE BED DEEP WELL.	PIPELINE MARKER	PLSS SECTION LINE	SPREAD BREAK									
PIPE ASSEMBLIES				PIPE COATING DATA				SPECIAL NOTES			ANODE BED DEEP WELL	HDD ENTRY / EXIT	ENVIRONMENTAL SURVEY AREA									