



DISCLAIMER: UNIVERSALPEGASUS INTERNATIONAL MAKES NO WARRANTY (EXPRESSED, IMPLIED OR OTHERWISE) THAT THE INFORMATION CONTAINED HEREIN IS ACCURATE OR COMPLETE AS TO ANY AND ALL SUBSURFACE CONDITIONS AND CONFORMATION. ANY RELIANCE CONTRACTOR PLACES ON THE INFORMATION CONTAINED HEREIN AS TO SUCH CONDITIONS, IS DONE SO AT ITS OWN RISK AND EXPENSE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE STATE "ONE CALL" SYSTEM PRIOR TO ANY EXCAVATION.

SURVEY DATA		STATIONING	
MATCHLINE 2450+00	MATCHLINE 2500+00	2460+21 FENCE CORNER RT 25	2483+59 FENCE CORNER RT 25
MATCHLINE 2450+00	MATCHLINE 2500+00	2450+20	2480+21
ENGINEERING DATA		MATERIAL	
REFERENCE DRAWING		2456+27	
CLASS LOCATION		2460+21	
MINIMUM DEPTH OF COVER		3'	
AC MITIGATION / CATHODIC PROTECTION		2470+21	
WATERBODY/WETLAND CROSSINGS		2473+62	
WATERBODY/WETLAND LENGTH		2480+21	
ENVIRONMENTAL DATA		STATIONS	
PERMANENT EROSION CONTROL		2484+63	
SLOPE BREAKER CODE		2480+21	
TOPSOIL SAVAGE		2484+63	
THREATENED AND ENDANGERED SPECIES		2480+21	
TIMING CONSTRAINT		2484+63	
CONSTRAINT 2		2480+21	
CONSTRAINT 3		2484+63	
CONSTRAINT 4		2480+21	

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS		GENERAL INFORMATION		REVISIONS				APPROVALS				
ITEM NO.	QTY	UOM	DESCRIPTION	QTY	UOM	REQN NUMBER	MATERIAL NUMBER	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.	NO.	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.
1	5000	FT	36" O.D. x 0.520" W.T., API 5L X70, PSL2, DSAW, 14-16 MILS FBE	4	EA			SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.	1	IFC (UPDATE ENV. RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG	PROJECT MANAGER	RG	MAINTENANCE OPERATION REGION
				3	EA			WARNING SIGNS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.	0	ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG	PROJECT DEF. NO.		MIN. TEST PRESSURE 1816 PSI
				1	EA			CP TEST STATION TYPE 1	21040-510-TYP-20028	CONTINUOUS CONCRETE COATING STANDARD FOR 36" / 30" PIPELINE	4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.									DESIGN PRESSURE 1440 PSI
				0	EA			CP TEST STATION TYPE 2	21040-510-TYP-20112	TYPICAL OPEN CUT / BORE	5. ADDITIONAL WARNING SIGNS MAY BE REQUIRED AS DICTATED BY CONSTRUCTION CONTRACT.									
				0	EA			AERIAL MARKERS	21040-510-TYP-20113	TYPICAL SADDLE BAG WEIGHTS	6. MAP PROJECTION: NAD 1983 HARN STATE PLANE FLORIDA EAST FIPS 0901 FEET. VERTICAL DATUM: NAVD 88.									
				0	EA			ANODE BED DEEP WELL	21040-510-TYP-20114	WARNING SIGN DETAIL	SPECIAL NOTES									
									21040-510-TYP-20115	AERIAL MARKER INSTALLATION DETAIL	1. INDUCTION BEND QUANTITIES ALONG WITH THEIR DESCRIPTIONS ARE LOCATED ON DRAWING 21040-505-FBW-00001.									
									21040-510-TYP-20116	AERIAL MARKER DETAIL	2. 3" - SEE ARK DRAWING PACKAGE FOR ANODE BED DEEP WELL.									
									21040-510-TYP-20117	TYPICAL PIPELINE MARKER ASSEMBLY										
									21040-510-TYP-20118	PIPELINE MARKER "WARNING" DECAL										