



**Table 5.04.07(E)(4). Design Standards for Permanent On-site signs.**

Sign Type:	Freestanding	Canopy	Wall	Awning	Projecting
Standard:					
Maximum sign face area	For non-residential zonings 5 s.f. per linear foot of frontage, to a maximum of 750 s.f. For residential zonings a maximum of thirty-two (32) s.f.	Fifty (50) square feet; or One (1) square foot per two (2) linear feet of canopy side	30% of each wall	20% of awning	24 s.f.
Sign location	Set back 5 feet from property line	N/A	Front, side, or rear facade	Front facade	Front facade sign shall not extend more than 4 feet from the building face
Maximum sign Height	35 feet, or 70 feet in C-H, M-1, or M-2 within 660 feet of I-75	N/A	N/A	Lowest part of awning must be a minimum of 8 feet above ground	Lowest part of sign must be a minimum of 8 feet above ground

**Proposed New Subsection H:**

**H. For any development arranged as a campus such as hospitals, educational facilities and religious facilities, incorporating three (3) or more buildings, the campus may be identified by a freestanding ground sign meeting the standards set forth in this section.**

- 1. The area of the sign may be increased above the standard set forth for freestanding signs in Table 5.04.07(E)(4) an additional five (5) square feet for each building on the campus, to a maximum sign face area of 1,000 square feet.**
- 2. A Campus with street frontage of 400 feet or more may have an additional freestanding sign for each 400 feet of frontage. Any**