

productive throughout their shift. Standard Non-cinching seat belts provide additional comfort in applications requiring frequent reverse travel.

**LCD MULTI-FUNCTION DISPLAY II**

Features on the new MFD II include data log functions, fuel information, & operation data log all with QR code output; fuel gauge (excluding LP); and password protected administrator level access that can manipulate functions such as travel, vehicle management, and operation data log functions.

---

---

**Mast** 3-Stage (FSV) mast with full free lift provides excellent visibility to load and fork tips, while providing smooth, quiet and consistent operation. Mast specifications:  
Maximum Fork Height - **189"**  
Overall Lowered Height - 84.4" (Overhead Guard Height - 81.90")  
Free Lift - 34.8" with standard Load Backrest

---

---

**Lifting Capacity** **Base Model Capacity - 3,000 lbs. @ 24" load center**  
**Actual Capacity, based on quoted specifications, - 2,750 lbs. @24" load center to 189" MFH**

*Actual capacity ratings stated above are based on standard features, options, and attachments available through Toyota at the time of quoting. Non-standard features, options, and attachments may affect actual capacity ratings. Please contact your Toyota sales representative for additional information.*

**Tilt** 6 degrees forward and 6 degrees backwards

**Carriage** ITA Hook Type, 36" Carriage

**Forks** "Forks 48" x 4" x 1.4" - Class II"

**Load Backrest** 48" High Load Backrest

**Attachments** Cascade 36"Side shifting Fork Positioner (Includes 3rd & 4<sup>th</sup> Function Internal Hosing)

**Speeds** Travel Speed: 11.80 mph Lift Speed: 125 fpm

**Engine** Toyota 2.2L 4Y-ECS Industrial Gasoline Engine  
136 cubic inch displacement, 4 cylinder, overhead valve (OHV)  
Net Torque Rating: 118 @ 2000 rpm SAE ft-lb  
Net Horsepower Rating: 48 @ 2250 rpm SAE HP

**Transmission** Automatic Transmission  
1 speed forward, 1 speed reverse standard.

**Steering** Load Sensing Hydrostatic Power Steering with Tilt Steering Column

**Wheels and Tires** Front Tires: 6.50-10-10PR (Pneumatic)  
Rear Tires: 5.00-8-8PR (Pneumatic)